



MEKP

Methyl Ethyl Ketone Peroxide

LIQUID CATALYST

for Polyester Resin

Follow mixing Instructions on
TAP Polyester Resin container.

DANGER: ORGANIC PEROXIDE. Vapor Harmful. Irritant.
Causes Severe Burns. Harmful or Fatal If Swallowed.
See Cautions on Back Panel.

Net 10 fl oz

Use with 5 Gallons Polyester Resin

TAP Plastics Inc. • San Leandro CA 94577
www.tapplastics.com

DANGER: ORGANIC PEROXIDE. Oxidizing material. Keep away from heat and fire. Do not store with food or drink. Wear chemical splash goggles, protective clothing, and rubber gloves.

KEEP OUT OF REACH OF CHILDREN.

Swallowing: Obtain medical attention. If patient is fully conscious, rinse mouth with water. Give water to drink. Drink water in small sips. (Diluting effect) Never give anything by mouth to an unconscious person. Vomiting may cause aspiration into the lungs resulting in chemical pneumonia.

Inhalation: Remove to fresh air. If exposure is severe, hospitalize and observe. If breathing has stopped, give artificial respiration.

Skin Contact: Remove contaminated clothing. Wash skin with soap and water. If irritation persists or if contact has been prolonged, obtain medical attention.

Eye Contact: Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention immediately. May cause blindness.

STORE REQUIREMENTS: Regulated as an Organic Peroxide, Class 5.2, for storage and handling. Store in original containers away from materials, direct sunlight, flames, and all sources of heat. Maximum storage temperature: 38° C (100° F). In order to maintain the product's original manufactured assay in long term storage, a lower storage temperature of below 30° C (86° F) is strongly recommended. Shelf life: Estimate > 48 months at which 95% of the original manufactured assay remains when stored at or below 30° C (86° F).

DATE CODE: 23017