## Typical Physical Properties of PVC Sheets

PROPERTIES	TEST METHOD	UNIT	INTEDUR Type 1	
PHYSICAL				
Thickness	ASTIM D1505	in.	1/16" ~ 1/2"	
Density	ASTM D792	g/cm³	1.36 ~ 1.40	
MECHANICAL				
Tensile Strength @ Yield	ASTM D638	psi	8,000 ~ 9,000	
Elongation @ Break	ASTM D638	%	25 ~ 45	
Flexural Modulus	ASTM D790	psi	380,000 ~ 430,000	
Flexural Strength @ Yield	ASTM D790	psi	7,000 ~ 13,000	
Izod Impact Strength (Notched)	ASTM D256	ft. lb./in.	0.8 ~ 2.5	
Shore Hardness (D scale)	ASTM D2240	D	75 ~ 84	
THERMAL				
Heat Deflection Temperature	ASTM D648	F	145 ~ 155	
Vertical Burn Test	UL 94	_	V-O	
REMARKS:		_		

(610) \*The above properties may vary slightly due to different sheet thicknesses.

The information contained herein is, to our best knowledge, true and accurate, but all recommendation or suggestion are made without guarantee. It is intended for use by person having technical skill and at their own discretion and risk. Because condictions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

January 2016



Visit our website: tapplastics.com

## Chemical Resistance of PVC Sheets

REGENT	CODE	REGENT	CODE
Glacial Acetic Acid	2	Turpentine	1
Hydrogen Peroxide (30%)	1	Sodium Carbonate Solution (20%)	1
Acetone	4	Toluene	4
Hydrofluoric Acid (40%)	1	Methyl Alcohol	1
Ammonium Hydroxide	1	Sulfuric Acid (Concentrate)	1
(Concentrate)			
Carbon Tetrachloride Carbon Tetrachloride	3	Citirc Acid (10%)	1
Most Detergents	1	Ethyl Alcohol	1
Seed or Minerals Oils	1	Ethyl Acetate	4

## **Resistance Codes:**

- 1 Inert
- 2 Limited
- 3 Very Limited
- 4 Non Resistant

January 2016



Visit our website: tapplastics.com